

Non-Piling Additive

Non-Piling Additive is especially for use on web presses, where blanket piling occurs due to excessive paper lint, or other impurities being generated in and around the web press. Non-Piling Additive will prevent blanket piling by adding just a small amount of the product directly to the water circulation tanks, at the beginning of each work shift. The press operators can now concentrate on printing and do not need to frequently stop the press to clean blankets.

Advantages:

- Will eliminate and control blanket piling
- Will help to increase productivity
- Will eliminate paper waste
- Economic to use

Recommendations for use:

Add about 200 ml. to the water circulation tank at the beginning of each work shift. Observe that blanket piling is under control, if a slight blanket piling problem still persists, then add an additional 100 ml. of Non-Piling Additive to the water circulation tank, and the blanket piling problem should now be under control for the entire work shift. Add more Non-Piling Additive as and when required.

Physical and chemical properties:

Appearance: Liquid
Solubility: Completely soluble in water
VOC: 515 g/l

Colour: Clear
Boiling point: 100 C
pH concentrate: 6.6

Odour: No particular odour
Relative density: 1.06 @ 20 C
Flash point: >115 C

Packaging: 1 liter / 1 box x 12 liters

防成块添加剂

Non Piling Additive(防成块添加剂) 尤其适用于卷筒纸轮转印刷机, 因为这些印刷机内及其周围易产生过多纸毛或其他杂质, 进而导致橡皮布堆墨。在每个工作班次开始时, 直接往水循环槽中加入少量添加剂, 即可防止橡皮布堆墨发生。这样, 印刷机操作员可集中精力印刷, 而不需要经常停止印刷机来清洁橡皮布。

优点:

- 消除和控制橡皮布堆墨;
- 消除纸张浪费;
- 有助于提高生产力;
- 使用经济。

使用说明:

每个工作班次开始时, 往水循环槽内加入约200毫升添加剂; 然后观察橡皮布堆墨是否得到控制, 如果仍出现轻微橡皮布堆积问题, 则往槽内再加入100毫升添加剂, 此时, 整个工作班次的橡皮布堆墨问题应该已得到控制了。需要时, 可添加更多添加剂。

外观: 液体

气味: 无特别气味

沸点: 100 C

VOC: 515 g/l

闪点: >115 C

颜色: 透明

溶解性: 完全溶于水

相对密度: 20°C时1.06

pH值: 6.6

包装: 1 公升/瓶 12 瓶/箱

